



Pin	Description
1	input
5	+V _B
9	output
2.3.7.8	common

FEATURES >>

- Excellent linearity
- Extremely low noise
- Excellent return loss properties
- High reliability

DESCRIPTION

Hybrid amplifier module operating over a frequency range of 5 to 120 MHz at a voltage supply of +24V(DC)

QUICK REFERENCE DATA

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
G _p	power gain	f=10 MHz	24	-	25	dB
I _{tot}	total current consumption(DC)	V _B =24V	130	-	155	mA

LIMITING VALUES

In accordance with the Absolute Maximum Rating System

SYMBOL	PARAMETER	MIN.	MAX.	UNITS
V _i	RF input voltage	-	55	dBmV
T _{stg}	storage temperature	-40	+100	°C
T _{mb}	operating mounting base temperature	-20	+90	°C

CHARACTERISTICS

 (Bandwidth 5 to 120MHz; $T_{mb}=30^{\circ}\text{C}$, $V_B=24\text{V}$, $Z_S=Z_L=75\Omega$)

PART NUMBER			Ei1202424R			
SYMBOL	PARAMETER	UNIT	MIN.	TYP.	MAX.	CONDITIONS
G_P	power gain	dB	24	-	25	f=10MHz
SL	slope cable equivalent	dB	-0.2	-	0.5	f=5 to 120 MHz
FL	flatness of frequency response	dB	-	-	± 0.2	f=5 to 120 MHz
S_{11}	input return loss	dB	-	-	-18	f=10 to 120 MHz
S_{22}	output return loss	dB	-	-	-18	f=10 to 120 MHz
CTB	composite triple beat	dB	-	-	-65	14 channel
CSO	composite second order distortion	dB	-	-	-65	$V_o=50\text{dBmV}$
X_{mod}	cross modulation	dB	-	-	-60	measured at 67.25MHz
V_o	output voltage	dBmV	60	-	-	$d_m=-60\text{dB}$
F	noise figure	dB	-	-	5	f=120 MHz
I_{tot}	total current consumption(DC)	mA	130	-	155	$V_B=+24\text{V}$

 The module normally operates at $V_B=24\text{V} (\pm 0.5)$.

MODULE DIMENSIONS
