




OUTLINE

PIN CONFIGURATION



FEATURES ➤

- Excellent linearity
- Extremely low noise
- Excellent return loss properties
- High gain
- High reliability

Pin

Description

1

input

5

+V_B

9

output

2.3.7.8

common

► DESCRIPTION

Hybrid amplifier module operating over a frequency range of 40 to 1003 MHz at a voltage supply of +24V(DC) ,employing GaAs MMIC.

QUICK REFERENCE DATA

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
G _p	power gain	f=50 MHz	26	27	27.5	dB
G _p	power gain	f=1003MHz	26.8	-	28.5	dB
I _{tot}	total current consumption(DC)	V _B =24V	270	-	330	mA

LIMITING VALUES

In accordance with the Absolute Maximum Rating System

SYMBOL	PARAMETER	MIN.	MAX.	UNITS
V _i	RF input voltage	-	55	dBmV
T _{stg}	storage temperature	-40	+100	°C
T _{mb}	operating mounting base temperature	-20	+90	°C

CHARACTERISTICS

(Bandwidth 40 to 1003MHz; $T_{mb}=25^{\circ}\text{C}$, $V_B=24\text{V}$, $Z_S=Z_L=75\Omega$)

PART NUMBER			Egi10002724P1			
SYMBOL	PARAMETER	UNIT	MIN.	TYP.	MAX.	CONDITIONS
G_P	power gain	dB	26	27	27.5	$f = 50\text{MHz}$
SL	slope cable equivalent	dB	1.0	2	2.5	$f = 50 \text{ to } 1003 \text{ MHz}$
FL	flatness of frequency response	dB	-	-	± 0.5	$f = 40 \text{ to } 1003 \text{ MHz}$
$S_{11} \& S_{22}$	Input & output return loss	dB	-	-	-16	$f = 40 \text{ to } 860 \text{ MHz}$
$S_{11} \& S_{22}$	Input & output return loss	dB	-	-	-12	$f = 860 \text{ to } 1003 \text{ MHz}$
CTB	composite triple beat	dB	-	-	-63	110 channel
CSO	composite second order distortion	dB	-	-	-61	$V_o=43\text{dBmV}$ at 745.25MHz
X_{mod}	cross modulation	dB	-	-	-58	flatness across the band
F	noise figure	dB	-	-	5.0	$f=860 \text{ MHz}$
I_{tot}	total current consumption(DC)	mA	270	-	310	$V_B=+24\text{V}$

The module normally operates at $V_B=24\text{V}(\pm 0.5)$.

MODULE DIMENSIONS

